



single mode four channel  
fibre optic video transmission  
system with a choice of  
data configurations

point to point cctv fibre optic solutions

## Guardian-Lite™ 2740 Series

### APPLICATIONS

- Security and surveillance
- Transportation
  - Road
  - Rail
  - Metro
  - Light rail
- Industrial Sites
- Inter and Intra Town & City Centres
- Campus Sites
- Video Conferencing
- Personnel Help Points
- Government Agency Applications

### FEATURES

#### Real Time Digital Transmission Format

No signal quality degradation with distance

#### Wide Link Dynamic Range

No link margin required for installation, just plug in and switch on

#### Single Fibre Operation

Reduced infrastructure requirement

#### Multiple Simultaneous Video plus Data Transmission

Enables remote control of camera functions plus bi-directional data

#### Plug-in Module for Standard AMG2000 19" Subrack

Ability to mix multimode and singlemode product in the same rack

#### Front Panel LED Status Indicators

At a glance status monitoring

#### Data Interface Daughter Board Configurable

Ability to address any interface protocol


#### Standalone and Rackmount Formats

Minimum space usage

#### Unlimited Repeat

For long distance transmissions

### CONFIGURATION OPTIONS



For Drop & Insert and repeater applications contact AMG

+



## SPECIFICATIONS

### Video

Input/Output level	1V pk to pk +3dB overload
Input/Output impedance	75 Ohm unbalanced
Frequency Response	10 Hz to 5.75 MHz min (7.5 MHz cut-off)
Differential gain	2% nominal
Differential phase	2° nominal
Signal to Noise Ratio	67dB (10 Bit Digitisation)

### Data

Data Rates	Up to 156 kB/s.
Data Interface Options	1 channel of RS422 or RS485 selected by internal switches.
Data Connectors	Plug in screw connectors

### Optical

Wavelength	1310/1550nm
Fibre dimensions	Singlemode (multimode option available)
Fibre Core Quantity	One required
Optical connector type	FC/PC on rear panel
Path loss	13dB min (greater path loss available)

### General

Operating Temperature	-15 to +65 C
Operating Humidity	0 to 95% non condensing
Video connectors	BNC
Emissions	CE Approved
Mechanical	3U x 7HP x 170mm (Plug-in or Standalone Module)
Power Requirements	+12v to +18v d.c @ 300mA
Indicators	Front panel LED status indicators

## PRODUCT ORDERING DETAILS

- AMG2741** - 4 Channel Video Only TX
- AMG2742** - 4 Channel Video Only RX
- AMG2743** - 4 Channel Video TX  
+ 1 Channel Data (RS232/422/485) TX/RX
- AMG2744** - 4 Channel Video RX  
+ 1 Channel Data (RS232/422/485) TX/RX

### RACKMOUNT UNITS

For the Rackmount Option add 'R' suffix to Part Number, e.g. **AMG2741R**

AMG Systems Limited reserves the right to change the specification without notice. The information herein is believed to be reliable and accurate, however no responsibility is assumed by AMG Systems Limited for it's use.  
Document Number: D15040-02